

# Low Profile Fiber Optic Wall Mount Patch Panel — 2 Adapter Strips

**Description**

Wirewerks™ low profile fiber optic wall mount patch panel is designed for fiber interconnects and splicing while offering a discreet profile. The patch panel is made of 16 gauge cold rolled steel (CRS) with a black powder coated finish, and accepts two adapter strips. Adapter strips, or cassettes up to 48 fibers can be installed into the 2 LGX cut-outs using their push pin mechanism. Four self-sealing grommets accommodate multiple cable entrance and exits. This low profile patch panel features two separate doors which are lockable with key locks (not included, part number WW000014) to control access to the distribution or patch sides, providing additional network security.

**Features and Benefits**

|   |   |
|---|---|
| Low profile design for space saving   | Maximum capacity of 48 fiber  |
| Fits 2 LGX adapter strips, and cassettes  | Both doors are lockable to protect your network (key lock not included) |
| Fits 2 slim splice trays part number SPL-MSPL6 (not included). For technical reference, refer to PDS-0126 | Installation hardware and instruction manual included                   |
| 4 grommets to limit contaminant intrusion at the cable entrance points                                    |   |

**Applications**

|                         |                     |
|-------------------------|---------------------|
| Data center             | Equipment room      |
| Telecommunications room | Consolidation point |

**Certification and Compliance**

|                    |   |
|--------------------|---|
| TIA-569-B          | Commercial Building Standard for Telecommunications Pathways and Spaces.        |
| CEA/EIA-310-E      | Cabinets, Racks, Panels and Associated Equipment standard.                      |
| ANSI/TIA/EIA-606-A | Administration Standard for Telecommunications Infrastructure.                  |
| UL 94              | Tests for Flammability of Plastic Material for Parts in Devices and Appliances. |
| RoHS               | Directive on Restriction of Hazardous Substances.                               |



# Low Profile Fiber Optic Wall Mount Patch Panel - 2 Adapter Strips



| <b>Ordering Information</b>       | Description   | Part Number  |
|-----------------------------------|---|--|
|                                   | Low profile fiber optic wall mount patch panel 2 adapter strips.  | PP-WM2S  |
| <b>Packaging</b>                  | Description   |  |
|                                   | Cardboard box, 1 unit per box.  |  |
| <b>Inclusion</b>                  | Description   |  |
|                                   | 1 instruction manual, 4 wood screws 10 x 0.75 inch, 2 nylon tie wraps, 4 Velcro tie wraps 11.8 inches long, 1 self-adhesive port ID label, 1 warning label. |  |
| <b>Physical Characteristics</b>   | Parameter   | Value  |
|                                   | Fiber count capacity  | 48 fibers maximum  |
|                                   | Plastic materials   | UL 94V-0 thermoplastic                                     |
|                                   | Panel material  | 16 Gauge cold rolled steel (CRS)                           |
|                                   | Panel finish  | Black Sandex   |
|                                   | Overall dimensions  | 381.6 mm (15.625 in) x 330.2 mm (13 in) x 54 mm (2.125 in) |
| <b>Mechanical Characteristics</b> | Parameter   | Value  |
|                                   | Installation temperature  | -25° C (-13° F) ~ 40° C (104° F)                           |
|                                   | Storage temperature   | -25° C (-13° F) ~ 55° C (131° F)                           |
|                                   | Relative humidity   | ≤ 85% (30° C)  |