Closet Splice Housing (CSH) 3 rack units, holds (12) 0.2-in splice trays

Part Number:
CSH-03U

Corning closet splice housing (CSH) provides storage and protection of fiber splices in individually accessible trays. The housings are used in equipment racks or equipment cabinets, 19 in (48 cm) or 23 in (58 cm), and in the transition splice between outdoor-rated and riser/plenum-rated cable at a building entrance. Pigtail splicing is accomplished when the CSH is used in conjunction with a rack-mount housing. The CSH is available in 3-rack-space tall and 5-rack-space models. A sliding shelf provides access to splice trays and routing guides. The housing has top and bottom rear removable access panels for vertical pigtail entry from the CLSSC-03U or CLSSC-04U housings and lockable front and rear doors (with the optional lock kits).

Features and Benefits

Universal cable clamp
Cable strain-relief

Open-side design
Easy fiber egress

Projection- or flush-mountable
Various installation options

Multiple grommeted cable entry ports
Installation options and protection

Closet Splice Housing (CSH) 3 rack units, holds (12) 0.2-in splice trays

Specifications

General Specifications	
Product Type	Housings

Standards	
RoHS	Free of hazardous substances according to RoHS 2011/65/EU

Design	
Lockable	Yes
Housing Type	Closet Splice Housing (CSH)
Splice Tray Options	Up to 12 category 2R, 2S or 2M
Lock Position	Front or rear

Design - Adapter	
Housing Color	Black

Connector Specs	
Housing Color	Black

Dimensions	
Height	133 mm (5.24 in)
Width	432 mm (17.01 in)
Depth	305 mm (12.01 in)

Ordering Information	
Product Number	CSH-03U

Closet Splice Housing (CSH) 3 rack units, holds (12) 0.2-in splice trays

Ordering Information	
Height Unit	3 U
Package Contents	Closet Splice Housing 3U; Installation guide; 4 blank panels; Installation Kit; UCC Kit; #12-24 and #10-32 mounting screws, Cage Nut Mounting Kit, Spiral Wrap, Tie Wraps
Shipping Weight	2.7 kg
Units per Delivery	1/1

RoHS COMPLIANT

Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2026 Corning Optical Communications. All rights reserved.