Spider Fan-Out Kit Insert, 3.0 mm, 250 µm

6 F, orange



Corning Cable Systems Spider Fan-Out Kits provide a low-cost furcation option for multifiber cables. Offering the end user simple step-by-step assembly, these kits are designed for factory and field furcation of 4- to 24- fiber tight-buffered and loose tube non-armored cables into 2.0 mm or 2.9 mm jacketed legs and eliminate the need for patch panels. The spider fan-out kit furcates and provides pull-out protection for bare fibers (900 µm or 250 µm). The cable jacket is simply stripped back and the fibers are threaded into the modular 6-fiber fan-out inserts consisting of six 1 m lengths of fan-out tubing secured in a composite assembly.

Comprised of an inner tube, an aramid yarn strength member and an outer protective PVDF jacket, the fan-out tubing provides three layers of protection. The fan-out insert then snaps into the main spider housing. When all the inserts have been loaded, the outer housing is installed to complete the assembly.

See the Resources tab, located on the individual part number pages, for the **Spider Fan-Out Kits Quick Reference Guide.** It will show you how to properly order/configure your spider fan-out kit part number.



Features and Benefits

Snap-together fan-out insert

Easy installation

Three-layer protective tubing

Fiber protection

Designed for factory and field furcation

Eliminates need for patch panel

Specifications

General Specifications	
Environment	Indoor
Fanout Type	Spider
Product Type	Fan-Out Kits



Spider Fan-Out Kit Insert, 3.0 mm, 250 µm

6 F, orange



Design	
Cable Type	Cable with 250 µm fiber
Fiber Count	6
Fan-Out Tubing Color	Orange

Mechanical Specifications - Fan-Out Kit	
Tubing Length	1,000 mm (39.4 in)
Tubing Outer Diameter	3 mm

Mechanical Characteristics	
Weight	68.04 kg (0.15 lb)

Chemical Characteristics	
RoHS	Free of hazardous substances according to RoHS 2002/95/ EG

Ordering Information

Part Number	INS-06F-250-3-O
Product Description	Spider Fan-Out insert for six 250 μm multimode fibers, 50 μm (OM2) or 62.5 μm (OM1), orange

Shipping Information

Units per Delivery	1/1
Package Contents	Spider fan-out insert with orange tubing, 3.0 mm



Corning Cable Systems LLC • PO Box 489 • Hickory, NC 28603-0489 USA 800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/cablesystems

A complete listing of the trademarks of Corning Cable Systems is available at www.corning.com/cablesystems/trademarks.

Corning Cable Systems is ISO 9001 certified. © 2012 Corning Cable Systems. All rights reserved.

